





# MATERIAL REQUIREMENTS

ALL MEASUREMENTS SHOWN ARE IN MILLIMETRES, HEIGHT X WIDTH IMAGES ARE NOT TO SCALE

# **DISPLAY ADVERTISING**





# **SPECIFICATIONS**

#### **PDFs**

- Please supply PDF files to the PDF/X-3 standard.
- · Resolution is 300 dpi.
- · All fonts must be embedded in the PDF.

Fonts must be active on your system at the time of pdf creation.

#### **Image specifications**

- Image resolution is 300dpi. All colours must be set to CMYK.
- Do not enlarge images more than 25%
- · Check all linked images are updated.

#### **Document specifications**

- Digital files must be prepared to the correct final size check that type, trim and bleed areas are correct.
- Ensure all live elements you wish to print are kept within the type area.
- Bleed provide 5mm of bleed where bleed is required.
  Check that crop marks are visible.

#### **Colour specifications**

- All colours to be set to CMYK no RGB.
- For a rich solid black use 100% Black plus 40% Cyan.

Never use 100% of all four colours.

- Total sum density (total ink weight) to fall between 280% & 300%.
- Convert all spot colours to CMYK.
- Black text level type should be 100% black only.

#### Fonts

• nextmedia supports Open type fonts and PC Postscript fonts only.

### **Applications supported**

• InDesign, Photoshop, Illustrator, Word docs, Text docs, PDF.

## **DELIVERY OPTIONS**

- · Quickcut to nextmedia (preferable)
- Websend or Dropbox
- Hightail (previously YouSendIt) www.hightail.com

### **EMAIL**

We accept email files under 30mb. Please note the booking number and magazine title in the subject field and email to adops@nextmedia.com.au

#### **CONTACT US**

Advertising Traffic Co-ordinator on (02) 9901 6100 or adops@nextmedia.com.au